




Typical section through external cavity wall.
Scale 1:20



Typical edge detail through up to 2.5m deep foundation with Anti-Heave.
Scale 1:20



Typical edge detail over 2.5m deep foundation with double Anti-Heave.
Scale 1:20



Plots 72-79, Block B, Flats.
Building 52.
Scale 1:50

GENERAL NOTES

- THIS DRAWING TO BE READ IN CONJUNCTION WITH ALL RELEVANT HEMSLEY CONSULTING AND SPECIALIST CONTRACTORS DOCUMENTS & SPECIFICATIONS PLUS PLANS AND DETAILS.
- REFER TO ARCHITECT'S SITE PLAN FOR ORIENTATION OF BUILDINGS.
- DIMENSIONS NOT TO BE SCALED.
- ALL WORK TO BE CARRIED OUT IN ACCORDANCE WITH ALL CURRENT REGULATIONS AND CODES OF PRACTICE AND IN ACCORDANCE WITH ALL APPROVED INSPECTORATE STANDARDS.
- FOUNDATION LEVEL TO BE INSPECTED BY RELEVANT INSPECTORS PRIOR TO PLACING CONCRETE.
- WHERE SHRINKABLE SOILS ARE ENCOUNTERED ALL FOUNDATIONS ARE TO BE IN ACCORDANCE WITH NHBC, STANDARDS CHAPTER 4.2 BUILDING NEAR TREES BASE ON HIGH SHRINKABILITY.
- SHOULD FOUNDATIONS HAVE TO DEEPEENED WITHIN THE INFLUENCE ZONE OF EXISTING TREES BEYOND 1.5m DEEP, THEN PROVIDE CLAYMASTER TO INSIDE FACE OF PERIMETER FOUNDATION THAT IS AFFECTED AS PER DETAIL.
- ALL CONCRETE TO FOOTINGS TO BE MINIMUM GRADE GEN 1 (ACEC) CLASSIFICATION AC-1 WITH A DESIGN SULPHATE CLASS FOR SITE OF DS-1 IN ACCORDANCE WITH BRE, SPECIAL DIGEST 1:2001.
- ALL NEW TREES (AS DEFINED IN NHBC, STANDARDS BUILDING NEAR TREES) TO BE PLANTED A MINIMUM DISTANCE FROM THE BUILDING OF:
-1.25 x MATURE HEIGHT FOR HIGH WATER DEMAND TREES.
-0.75 x MATURE HEIGHT FOR MODERATE WATER DEMAND TREES.
-0.5 x MATURE HEIGHT FOR LOW WATER DEMAND TREES.
- WHERE EXISTING BUILDINGS HAVE BEEN DEMOLISHED, FOUNDATIONS MAY HAVE TO BE DEEPEENED LOCALLY THROUGH THE DISTURBED GROUND ONTO A NATURAL STRATUM.
- ANY SOFT SPOTS IN FORMATION TO BE EXCAVATED AND INFILLED WITH LEAN MIX CONCRETE.
- SHOULD EXCAVATIONS BE REQUIRED BELOW GROUND WATER LEVEL, APPROPRIATE SHORING AND DEWATERING MEASURES SHOULD BE USED WITH CONTROL EMPLOYED TO PREVENT THE LOSS OF FINES.
- WHERE DRAIN TRENCH OR CHAMBER IS WITHIN 1m OF THE FOUNDATION, DEPTH OF FOUNDATION MUST BE TAKEN TO A MINIMUM OF THE INVERT LEVEL (IL) OF THE DRAIN OR CHAMBER AND / OR DRAIN MUST BE LAID IN ACCORDANCE TO CLAUSE 2.25 OF THE BUILDING REGULATIONS 2010 APPROVED DOCUMENT H, AND CURRENT EDITION OF SEWERS FOR ADOPTION.
- TOP OF CONCRETE LEVEL TO BE A MINIMUM OF 825mm FOR HOUSES AND 600mm FOR GARAGES.

CONSTRUCTION

C1	09.02.24	CONSTRUCTION ISSUE.
T06	17.01.24	FOUNDATION ARRANGEMENT REVISED.
T05	11.01.24	NEW SUBSTRUCTURE WALLS ADDED.
T04	06.10.23	FOR TENDER ISSUE, LEVELS REVISED.
T03	26.09.23	FOR TENDER ISSUE, LAYOUT REVISED TO LATEST ARCHITECTS ISSUE.
T02	21.09.23	FOR TENDER ISSUE.
T01	15.09.23	FOR TENDER ISSUE.
rev.	date	description

HEMSLEY CONSULTING LIMITED
CONSULTING STRUCTURAL & CIVIL ENGINEERS

Unit 9, Park Farm, Hundred Acre Lane
Wivelsfield Green, West Sussex, RH17 7RU
Tel. 01273 891738, Fax. 01273 891420
E. Mail: mail@hemsleyconsulting.com

client: **Thakeham**

project: **KEYMER ROAD, BURGESS HILL.**

title: **STAGE 02, PLOTS 72-79, BLOCK B, FLATS, BUILDING 52.**

date:	AUG-2023	scale:	1:50@A1	project no:	6164
drawn by:	RS.	checked:	T.J.H.	sheet size:	A1
drawing no:	H093-HCL-WD-B052-D-S-2000.	rev:			C1.

MINIMUM LAP AT FOUNDATION STEPS TO BE 1 METRE.

MINIMUM VOID BENEATH BEAM AND BLOCK FLOOR TO BE 300mm.

MINIMUM CONCRETE THICKNESS TO BE 500mm.

FOUNDATIONS TO PASS THROUGH ANY MADE GROUND / DISTURBED GROUND.